



Turnstile Gate

DE-FHSSTG-SL01



Product Descriptions:

Full Height Turnstile developed by DECS is available for any area which needs a high level of security without persons to monitor.

The machine is well designed to be rustproof, durable and able to resist external destroy.

Full Height Turnstile is normally designed to be Semi-Automatic Type, but we can also provide Full Automatic Type and Manual Type for customization.

Full Height Turnstile with 3-arm obstacle: the center rotor rotates 120 degrees per time, and it offers a comfortable space for users.

Full Height Turnstile with 4-arm obstacle: the center rotor rotates 90 degrees per time, and it offers a higher level of security but less space for users.

This series has 3-arm obstacle.



Function Specifications:

Both directions can be set as controlled mode or free mode.

NO mode & NC mode can be switched over by users easily & freely.

Self-recovery function: the machine will recovery automatically with Counting if passage is not completed within pre-set time (5 seconds default, adjustable By software).

With interface of relay switch (the dry contact signal or +12V electrical level signal

PRODUCT DESCRIPTION

DESCRIPTION	Details
Power Requirements-	(AC110V/220V, 50/60HZ)
Caging	Yes
Return Back Lock	Yes
Manual Rotation Lock	Yes
Working Humidity	(0 % TO 90 %)
Working Environment	INDOOR/OUTDOOR
LANE WIDTH (mm)	580 mm
LANE DEPTH (mm)	600 mm
RFID max. speed of Throughput	30 MINUTES
Footprint (mm x mm)	(1400mm X 1320 mm)
Dimension (mm)	(L=1400 , W=1320 and H= 2220)
LED indicator	Y
BARRIER material	SUS304 STAINLESS STEEL
BARRIER movement	ROTATING
EMERGENCY mode	Y
Security level	HIGH
Fingerprint max. speed of Throughput	25 MINUTES
FACE max. speed of Throughput	15 MINUTES
VEIN max. speed of Throughput	15 MINUTES
LANE WIDTH (mm)	580 mm
Footprint (mm x mm)	(1400mm X 1320 mm)
DESCRIPTION	MINIMUM SPECIFICATION



Dimension (mm)	(L=1400 , W=1320 and H= 2220)
Reqd. Dimension with packing(mm)	(1975x 925x 895 and 2100 x 1435 x 470)
LED indicator	Y
BARRIER material	SUS304 STAINLESS STEEL
BARRIER movement	ROTATING
EMERGENCY mode	Y
Security level	HIGH
MCFB	2 MILLION
INGRESS protection	IP54